

REQUEST FOR ACCESS C. ABANDONED APPLICATION UNDER 37 CFR 1.14(a)

PROCESSED BY

SEP 02 1999

FBI

In re Application of

Koenck

Application Number

879,4175
82,061

Filed

5/20/98

Group Art Unit

Examiner

Assistant Commissioner for Patents
Washington, DC 20231

Paper No.

#25

I hereby request access under 37 CFR 1.14(a)(3)(iv) to the application file record of the above-identified ABANDONED application, which is: (CHECK ONE)

- ☐ (A) referred to in United States Patent Number 5889386, column _____
- ☐ (B) referred to in an application that is open to public inspection as set forth in 37 CFR 1.11, i.e., Application No. _____, filed _____, on page _____ of paper number _____
- ☐ (C) an application that claims the benefit of the filing date of an application that is open to public inspection, i.e., Application No. _____, filed _____, or
- ☐ (D) an application in which the applicant has filed an authorization to lay open the complete application to the public.

Please direct any correspondence concerning this request to the following address:

Michael Holbert
Signature

9/2/99
Date

Typed or printed name

FOR PTO USE ONLY

Approved by: [Signature]

(initials)

Unit: Bill Information

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.



United States Patent [19]

Koenck

[11] **Patent Number:** **5,889,386**

[45] **Date of Patent:** Mar. 30, 1999

[54] BATTERY CONDITIONING SYSTEM
HAVING COMMUNICATION WITH
BATTERY PARAMETER MEMORY MEANS
IN CONJUNCTION WITH BATTERY
CONDITIONING

[75] Inventor: **Steven E. Koenck**, Cedar Rapids, Iowa

[73] Assignee: **Intermec Technology Corporation,**
Everett, Wash.

[21] Appl. No.: 82,061

[22] Filed: **May 20, 1998**

Related U.S. Application Data

[63] Continuation of Ser. No. 879,475, Jun. 20, 1997, which is a continuation of Ser. No. 561,665, Nov. 22, 1995, abandoned, which is a continuation of Ser. No. 134,881, Oct. 12, 1993, Pat. No. 5,508,599, which is a continuation of Ser. No. 769,337, Oct. 1, 1991, Pat. No. 5,278,487, which is a continuation of Ser. No. 544,230, Jun. 19, 1990, abandoned, which is a division of Ser. No. 422,226, Oct. 16, 1989, Pat. No. 4,961,043, which is a division of Ser. No. 168,352, Mar. 15, 1988, Pat. No. 4,885,523, which is a continuation-in-part of Ser. No. 944,503, Dec. 18, 1986, Pat. No. 4,737,702, which is a continuation-in-part of Ser. No. 876,194, Jun. 19, 1986, Pat. No. 4,709,202, which is a division of Ser. No. 797,235, Nov. 12, 1985, Pat. No. 4,716,354, which is a continuation-in-part of Ser. No. 612,588, May 21, 1984, Pat. No. 4,455,081, which is a continuation-in-part of Ser. No. 385,830, Jun. 7, 1982, Pat. No. 4,455,523.

[51] **Int. Cl.⁶** **H02J 7/00**

[52] U.S. Cl. 320/136; 320/107; 320/112;
320/114; 320/134; 320/427; 320/426

[58] **Field of Search** 320/107, 106,
320/112, 113, 114, 115, 116, 134, 136;
324/426-435

[56] References Cited

U.S. PATENT DOCUMENTS

3,971,980	7/1976	Jungfer et al. .
4,295,097	10/1981	Thompson et al. .
4,377,787	3/1983	Kikuoka et al. .

Primary Examiner—Edward H. Tso

Assistant Examiner—K. Shin

Attorney, Agent, or Firm—McAndrews, Held & Malloy,
Ltd.

[57] **ABSTRACT**

In an exemplary embodiment, a battery conditioning system monitors battery conditioning and includes a memory for storing data based thereon; for example, data may be stored representative of available battery capacity as measured during a deep discharge cycle. With a microprocessor monitoring battery operation of a portable unit, a measure of remaining battery capacity can be calculated and displayed. Where the microprocessor and battery conditioning system memory are permanently secured to the battery so as to receive operating power therefrom during storage and handling, the performance of a given battery in actual use can be accurately judged since the battery system can itself maintain a count of accumulated hours of use and other relevant parameters. In the case of a non-portable conditioning system, two-way communication may be established with a memory associated with the portable unit so that the portable unit can transmit to the conditioning system information concerning battery parameters (e.g. rated battery capacity) and/or battery usage (e.g. numbers of shallow discharge and recharge cycles), and after a conditioning operation, the conditioning system can transmit to the portable unit a measured value of battery capacity, for example.

20 Claims, 24 Drawing Sheets

